

PROJECT NAME: _____

LOCATION: _____

SPECIFIER ITEM NO. _____ **QTY:** _____



ENCORE PART NO. _____

Encore[®] Deck Mount 4" (102mm) Centerset
Faucet with Cast Spout and 4" (102mm)
Wrist Blade Handles

KL83-4x04-CE4 Series

KL83-4004-CE4 4" Spout, Compression Valves

KL83-4104-CE4 4" Spout, Ceramic Valves



*Dimensions shown in inches (mm) are for reference only
and are subject to change.*

1-1/8" (29mm) holes for deck are recommended to
accommodate 1/2" supply nipples

1/2" NPSM Male Inlets with Compression Fittings

Operating Temperature: 40-180°F (5-83°C)

Operating Pressure: 15-125psi

Approximate shipping weight - 5 lbs
Warranty - 2 years parts

Solid heavy duty cast body is specification and commercial quality

Commercial Quality Features

- Polished chrome plated cast brass body
- 4" (102mm) cast spout
- ADA-compliant 4" (102mm) wrist blade handles
- Built-in check valves to prevent cross-flow and back-flow

SPECIFICATIONS:

Deck Mount Centerset Faucet to be Encore KL83 Series
in the following configuration:

_____ KL83-4004-CE4 4" Spout, Compression Valves

_____ KL83-4104-CE4 4" Spout, Ceramic Valves

Faucet body to be constructed of polished chrome plated brass with wrist
blade handles. Valves to be 1/4-turn with integral check valve to prevent
cross-flow and back-flow. Color coded temperature indexes shall meet
international standards. Spout to be 4" (102mm) cast. 2.2gpm aerator
@60psi standard with full flow stream bubbler screenspout tip.

For a complete list of available options for KL83-4004-C Series,
see product configurator on reverse.

Faucet Configuration for KL83-4004-C Series

